

In the Claims:

Please amend claims 7 and 16-21 as follows:

1. (Canceled)
2. (Previously Presented) A display panel module comprising:
a display panel defining a screen on a front surface;
an electrically conducting frame enclosing the display panel; and
an electrically conductive member located behind the display panel and electrically connected to the electrically conductive frame, wherein
a loop line is established through the electrically conductive member and the electrically conductive frame, said loop line having a length different from a wavelength of a driving signal supplied to the display panel.
3. (Original) The display panel module according to claim 2, wherein said length of the loop line is set smaller than a half of the wavelength of the driving signal.
4. (Original) The display panel module according to claim 3, wherein electric joints are established between the electrically conductive member and the electrically

conductive frame at positions spaced by intervals smaller than a quarter of the wavelength of the driving signal.

5. (Original) The display panel module according to claim 2, wherein said length of the loop line is set smaller than a quarter of the wavelength of the driving signal.

6. (Original) The display panel module according to claim 5, wherein electric joints are established between the electrically conductive member and the electrically conductive frame at positions spaced by intervals smaller than one eighth of the wavelength of the driving signal.

7. (Currently Amended) A display panel module comprising:

a liquid crystal display panel defining a screen on a front surface;

a panel-shaped module component superposed on a rear surface of the liquid crystal display panel;

an electrically insulating bezel having a flat plate frame directly receiving a set of the liquid crystal display panel and the panel-shaped module component, and

an electrically insulating member coupled to the electrically insulating bezel so as to hold the liquid crystal display panel and the module component against the flat plate frame.

8. (Canceled)

9. (Previously Presented) The electronic apparatus according to claim 10, wherein said display panel, said module component and said electrically conductive frame form a display panel module.

10. (Previously Presented) An electronic apparatus comprising:
a display panel defining a screen on a front surface;
a panel-shaped module component superposed on a rear surface of the display panel;

an electrically conductive frame enclosing the display panel and the panel-shaped module component so as to couple the module component to the display panel; and

an electrically conductive member located behind the display panel and electrically connected to the electrically conductive frame wherein

a loop line is established through the electrically conductive member and the electrically conductive frame, said loop line having a length different from a wavelength of a driving signal supplied to the display panel.

11. (Original) The electronic apparatus according to claim 10, wherein said length of the loop line is set smaller than a half of the wavelength of the driving signal.

12. (Original) The electronic apparatus according to claim 11, wherein electric joints are established between the electrically conductive member and the electrically conductive frame at positions spaced by intervals smaller than a quarter of the wavelength of the driving signal.

13. (Original) The electronic apparatus according to claim 10, wherein said length of the loop line is set smaller than a quarter of the wavelength of the driving signal.

14. (Original) The electronic apparatus according to claim 13, wherein electric joints are established between the electrically conductive member and the electrically conductive frame at positions spaced by intervals smaller than one eighth of the wavelength of the driving signal.

15. (Previously Presented) The display panel module according to claim 7, wherein said module component comprises at least one of a diffuser, a prism plate, a light pipe, a light source and a reflector.

16. (Currently Amended) A display panel module comprising:
a liquid crystal display panel defining a screen on a front surface;
a panel-shaped module component opposed to a rear surface of the liquid crystal display panel, the panel-shaped module component excluding a metal frame; and
an electrically insulating bezel enclosing the liquid crystal display panel and the panel-shaped module component so as to couple the module component to the liquid crystal display panel.

17. (Currently Amended) An electronic apparatus comprising:
a housing; and
a display panel module incorporated within the housing, wherein the display panel module comprises:

a liquid crystal display panel defining a screen on a front surface;
a panel-shaped module component superposed on a rear surface of the liquid crystal display panel; and

an electrically insulating bezel enclosing the liquid crystal display panel and the panel-shaped module component so as to couple the module component to the liquid crystal display panel.

18. (Currently Amended) The display panel module according to claim 7, wherein said liquid crystal display panel includes a pair of glass substrates as outermost panels, liquid crystal cells being established between the substrates.

19. (Currently Amended) The display panel module according to claim 7, wherein the electrically insulating bezel receives the set of the liquid crystal display panel and the panel-shaped module component without disposition of an electrically-conductive frame in front of the liquid crystal display panel.

20. (Currently Amended) The display panel module according to claim 16, wherein the electrically insulating bezel encloses the liquid crystal display panel and the panel-shaped module component without disposition of an electrically-conductive frame in front of the liquid crystal display panel.

21. (Currently Amended) The electronic apparatus according to claim 17, wherein the electrically insulating bezel encloses the liquid crystal display panel and the

panel-shaped module component without disposition of an electrically-conductive frame in front of the liquid crystal display panel.